

# PRODUCT VERIFICATION FORM

Break-Safe® Load Break & Pick-up tools are selected based on System Voltage (Phase to Phase) and offered in multiple configurations. The 38kV 300A, 46kV 200A, and 27kV 600A are specialized tools for unique applications which made to-order and non-refundable.

Please complete the form to confirm the tool selection.

**NOTICE: ORDERS ARE NOT ENTERED UNTIL THE COMPLETED FORM IS VERIFIED.**

Technical support is available at [techsupport@utilityolutionsinc.com](mailto:techsupport@utilityolutionsinc.com).

**Part Number (circle one):**

USBS-38-1-PS-^ (38 kV 300 A with Floating Head BREAK-SAFE®)

USBS-38-2-PS-^ (38 kV 300 A with Duckbill Head BREAK-SAFE®)

^ Available with optional soft or hard case

USBS-46-1-PS-^ (46 kV 200 A with Floating Head BREAK-SAFE®)

USBS-46-2-PS-^ (46 kV 200 A with Duckbill Head BREAK-SAFE®)

^Available with optional soft or hard case

USBS-600-1-S (27 kV 600 A with Floating Head BREAK-SAFE® with Soft Case)

**Application Details**

\*15 kV & 27 kV 300 AMP tools do not require product verification. Reference [website](#) for more information.

System Voltage (Phase to Phase): \_\_\_\_\_ Load Currents (Amps): \_\_\_\_\_

Description of job: \_\_\_\_\_

**End User Information**

Company: \_\_\_\_\_ Contact: \_\_\_\_\_

Phone: \_\_\_\_\_ Email: \_\_\_\_\_

Is this your first BREAK-SAFE® Purchase (circle one): Yes No

**Email completed form to: [sales@utilityolutionsinc.com](mailto:sales@utilityolutionsinc.com)**

**or**

**Fax completed form to: 828-323-8410**